



Context Definitions for the OpenMP API Specification Version 5.0

Version 1.0 November 2018
Public Comment Draft
(expires February 7, 2019)

Copyright ©1997-2018 OpenMP Architecture Review Board.
Permission to copy without fee all or part of this material is granted, provided the OpenMP Architecture Review Board copyright notice and the title of this document appear. Notice is given that copying is by permission of OpenMP Architecture Review Board.

This page intentionally left blank

1 OpenMP 5.0 Context Definitions

This document describes additional values for OpenMP contexts that compliant implementations must support, as stated in Section 2.3.1 of the OpenMP 5.0 specification.

1.1 Additional *kind-name* Values

Table 1.1 describes the *kind-name* values that can be used in the **kind** trait of the OpenMP context in addition to the **host** and **nohost** values.

TABLE 1.1: Additional *kind-name* values

<i>kind-name</i>	Description
cpu	A parallel device optimized for general computation.
gpu	A massively parallel throughput device.
fpga	A reconfigurable computational device.

1.2 Additional *vendor-name* Values

Table 1.2 describes the *vendor-name* values that can be used in the **vendor** trait in the OpenMP context and their correspondence to the represented organization.

TABLE 1.2: Additional *vendor-name* values

<i>vendor-name</i>	Organization
amd	Advanced Micro Devices, Inc.
arm	Arm Limited

table continued on next page

table continued from previous page

<i>vendor-name</i>	Organization
bsc	Barcelona Supercomputing Center
cray	Cray Inc.
fujitsu	Fujitsu Limited
gnu	GNU Project
ibm	IBM Corporation
intel	Intel Corporation
llvm	LLVM Foundation
pgi	Portland Group
ti	Texas Instruments
unknown	Any other than those listed above

1